
MATERIAL SAFETY DATA SHEET

Page : 01

1 Identification of the substance / preparation and of the company / undertaking

- Product name:

OCI ORGASIL 103 ACETIC CURE SILICONE SEALANT

- Company:

OCI Berhad

Office:

3, Jalan Renggam 15/5,
Kawasan Perindustrian Seksyen 15,
40000 Shah Alam, Selangor, Malaysia.

Factory :

1, Jalan Halba Satu, 16/16A, Seksyen 16,
Kawasan Perindustrian Shah Alam,
40000 Shah Alam, Selangor, Malaysia.

Telephone: 603-77824277 , Fax: 603-77817896 (Office) 55148899 Fax: 603-55116278 (office)
Emergency Tel No: 603-55104997, Fax: 603-55104822 (Factory)

2 Composition / information on ingredients

Chemical Name	CAS No.	Proportion (%)
Dimethyl siloxane, Hydroxy-terminated	0701311678	> 60
Amorphous fumed silica	112945525	10-<30
Methyltriacetoxysilane	004253343	<10
Ethyltriacetoxysilane	017689779	<10

Further information:

This sheet only contains safety relevant data. For specific data, see Technical Data sheet.

3 Hazards identification

Evolution of acetic acid through action of water

4 First-aid measures

Take off immediately all contaminated clothing.

- After skin contact:

Clear with water and skin cleanser immediately.

- After eyes contact:

Rinse with plenty of water immediately, seek medical advice if necessary.

- After ingestion:

Seek medical advice immediately.

5 Fire-fighting measures

- Suitable extinguishing media:

water spray, foam, CO₂, dry powder

- Unsuitable extinguishing media: -

MATERIAL SAFETY DATA SHEET

Page : 02

6 Accidental release measures

- Methods for cleaning up,
Take up mechanically.

7 Handling and storage

- Handling:
Ensure good ventilating during processing.
- Protection against fire / explosion:
General rules of fire prevention should be observed.
- Storage:
Keep container tightly closed and dry. Store in a well-ventilated area.

8 Exposure controls / personal protection

- Ingredients with limiting values to be controlled.
TLV (TRGS 900/D): not indicated
- Industrial hygiene:
Remove immediately all contaminated clothing. Do not inhale vapours / aerosols.
- Hand protection:
Suitable protective gloves
- Eye protection:
protective goggles

9 Physical and chemical properties

- Form: pasty
- Colour: clear, white, black, grey, aluminum and brown
- Odour: pungent of acetic acid
- Melting temperature not applicable
- Boiling temperature (hPa) not applicable
- Flash point > 320 °C
- Ignition temperature not determined
- Vapour pressure (20°C) 15hPa (acetic acid)
- Density (20°C) 1, 2 - 1,3g/cm³
- Solubility in water (20°C) practically insoluble
- pH Value (g/l water) (°C) not determined

10 Stability and reactivity

- Stability
decomposition at temperature above 250°C
- Hazardous decomposition products:
acetic acid in case of hydrolysis
- Hazardous reaction:C115
No dangerous reactions known

MATERIAL SAFETY DATA SHEET

Page : 03

11 Toxicological information

- Skin:
may cause moderate irritation. Repeated skin contact may cause allergic skin reaction.
- Eyes:
possibly irritating
- Inhaled:
Irritates respiratory passages very slightly.

12 Ecological information

No data available (preparation)

13 Disposal considerations

- Product:
With respect to local regulations, e.g. dispose of to suitable waste incineration plant.

14 Transport information

15 Regulatory information

- Labeling (EC):
Not subject to labeling provisions by directive 67/548/EEC

16 Other information

The details contained herein are based on our present state of knowledge and experience and are to characterize our product with regard to any possible safety requirement. We do, however, pass them on without any warranty or property assurances.